

MILWAUKEE TOOL

Milwaukee Electric Tool Corporation BROOKFIELD, WI 53005

Tel: +1 (262) 781-3600 • Fax: +1 (262) 790-6333

Milwaukee Asia Office 29/F, Tower 2, Kowloon Commerce Centre, 51 Kwai Cheong Road, Kwai Chung, Hong Kong Tel: +852-2492-2181 • Fax: +852-2490-4778

Distributed by:

20/3/2020


All data incl. service and warranty conditions as well as product range are subject to change without notice. Pictures not binding. No liability for printing errors or mistakes. © 2019 Milwaukee Electric Tool Corporation.

All trademarks are owned by Techtronic Cordless GP unless otherwise stated.

www.milwaukeetool.asia



DRIVEN TO OUTPERFORM.



M12 FDGS
M12 FUEL
STRAIGHT
DIE
GRINDER

MORE
POWER
THAN
PNEUMATIC

3-MODE SPEED CONTROL

GREATER
MOBILITY
& ACCESS



DRIVEN TO OUTPERFORM.

M12 FUEL is engineered for the most demanding tradesmen in the world. M12 FUEL delivers unrivaled performance in a compact structure and features three MILWAUKEE exclusive innovations - the POWERSTATE Brushless Motor, REDLITHIUM-ION Battery Pack and REDLINK PLUS Intelligence Hardware and Software - that deliver unmatched power, run-time and durability. Simply put, the M12 FUEL Straight Die Grinder is the only cordless straight die grinder that delivers the performance service mechanics and professional metal workers demand.


M12 FUEL



283MM LENGTH


M12 FUEL STRAIGHT DIE GRINDER

MORE POWER THAN PNEUMATIC



■ More powerful than pneumatic 0.25 HP die grinders

3-MODE SPEED CONTROL



■ Optimized for most common 2" accessories

■ Dial in the right max RPM for safer operation

Variable speed trigger

GREATER MOBILITY & ACCESS



- No air hoses, compressors, or daily maintenance
- Increased cost savings over pneumatic power

		PX		0	
	CARBIDE BURR	BUFFING Stone	FLAP WHEEL*	CUT OFF WHEEL**	WIRE WHEEL
1"	✓	✓	✓	N/A	/
2"	N/A	N/A	✓	/	✓
3"	N/A	N/A	x	X	X

*For best performance, let the tool do the work and apply appropriate pressure as necessary

**For best performance, use high quality and balanced accessories (such as MILWAUKEE or Pferd) while applying appropriate pressure as necessary

SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS	DESCRIPTION	SPECIFICATIONS
Collet Size	6.0 mm & 8.0 mm	3-Mode RPM Control	10,000 / 15,000 / 21,000 rpm
Length	283 mm	Weight (w/3.0Ah battery)	0.8 kg